



GLATT GC-750/500 - COATING UNIT



 Customers rate us on Guaranteed Reviews Company, have a look at their feedback.

SKU: 11812 | **Categories:** [Coating pan / coater](#)

PRODUCT DESCRIPTION

A full coating unit, with its equipment, designed for coating products by means of a continuous or discontinuous spraying process.

ADDITIONAL DOCUMENTS :

[Plan implantation équipements + système cip . pdf](#)



1 GLATT GC 750/500 COATING UNIT

- drive motor : 1,1 kW - 380 V - 50 hz - IP 54 - Ex
- ventilateur d'entrée d'air : 1000 m³/h - 6860 trs/min - 2'003 Pa - Max 80°C - 1,1 kW - IP 54
- air inlet fan : 1000 m³/h - 6860 rpm - 2'003 Pa - Max 80°C - 1,1 kW - IP 54
- air outlet fan: 1200 m³/h - 2900 rpm - 1'030 Pa - Max 80°C - 7,5 kW - IP 55
- Drum speed: 2 - 18 rpm
- Sold with two perforated drums ø500mm and ø750 mm
- Adaptable 2-head spray arm + Peristaltic pump
- Spare parts, seals, ...
- Capacity :
20L : 7 to 15 kg
60L : 30 to 45 kg

1 DUST COLLECTOR HERDING FILTERTECHNIK

Extraction air volume: 1200 m³ / h

EXTRACTION AIR VOLUME: 1200 M³ / H

1 WANSON CD-36 STEAM BOILER

- Power: 36 kW
- Steam output: 48 kg/h
- Operating pressure: 5 bar
- Temperature : 159°C
- Water volume: 10 L

1 CLEANING SYSTEM (CIP)

Used for easy cleaning and maintenance of the machine.













