



IMMEQUIP CEMH-LAM360 - CUTTER / LAMINATOR



 Customers rate us on Guaranteed Reviews Company, [have a look at their feedback.](#)

SKU: 12405-1 | **Categories:** [Cutter / slicer / chopper](#), [Mill / Grinder](#)

PRODUCT DESCRIPTION

Manufacturer : IMMEQUIP Engineering

Model : CEMH-LAM360

Year : 2021

Type : Cutter / Laminator

Structure & design: All-stainless steel 304L mechanically welded frame
Fitted with 4 pivoting wheels with brakes

Dimensions

Longueur totale : 3550 mm

Hauteur tapis entrée : 1025 mm (± 15 mm réglable)

Hauteur tapis sortie : 737 mm

Largeur bandes : 360 mm

Conveyor: Infeed conveyor

- White silicone NEOBELTING belt



- Maximum temperature: 90°C continuous
- Speed: 17 m/min
- Motor: 0.25 kW – three-phase 400V
- Option not supplied with the machine, available on request: product guidance via stainless steel comb + pressure rollers

Conveyor system: Exit conveyor

- White silicone NEOBELTING belt
- Speed: 43 m/min
- Motor: 0.37 kW – three-phase 400V
- Integrated air blow-off ramp

Cutting unit

- Cutting wheel Ø350 mm
- 3 blade holders (45° and 90°)
- 3 ground hardened steel blades (Z30C13 – 40/42 HRC) – additional blades can be fitted
- Rotational speed: 72 rpm
- Motor: 0.37 kW – three-phase 400V
- Stainless steel housing with adjustable pressure roller
- Stainless steel roller guide
- Cutting kit available: 90° and 45°

Product orientation kit: 2 symmetrical sets, each comprising 1 cell, 1 stop flap and 1 pneumatic cylinder

Rolling function

- Non-motorised hollow stainless steel roller, Ø140 x 350 mm
- Gap adjustment: manual
- Adjustable anti-clogging scraper

Power supply: Three-phase 400V – 50 Hz

Danfoss VLT frequency converters

Operator display (HMI)

Full machine control

Buzzer + power-on indicator light

Emergency stop buttons (including 1 on the cutting unit side)

Electrical documentation available



